



6859 Renoir Avenue  
Baton Rouge, LA 70806

Tel: (225) 924-3221  
Fax: (225) 927-2918

## **LEWCO 1500 SA-2**

### **Silicone Impregnated Fiberglass Fabric**

---

#### **Product Specifications**

LEWCO Style 1500 SA-2 is our low cost, asbestos free woven fiberglass fabric impregnated with a special chemical, water and oil resistant silicone rubber. LEWCO Style 1500 SA-2 is a flexible, light to medium weight fabric for removable insulation blankets.

#### **Typical Properties**

|                                  |                  |
|----------------------------------|------------------|
| E Glass Melting Point            | 1523 ° F         |
| Maximum Continuous Temperature   | 1100 ° F         |
| Maximum Temp of Silicone Coating | 500 ° F          |
| Minimum Temperature              | -80 ° F          |
| Color                            | Silver           |
| Type Fiberglass                  | E Glass          |
| Weight                           | 15 Oz./Sq. Yd.   |
| Thickness                        | .016 Inches      |
| Width                            | 60 Inches        |
| Tensile Strength                 | 580 * 385<br>W F |

---

This information is given in good faith and is believed to be accurate. It is intended for use by persons skilled in the art of fabricating and applying removable/reusable insulation or like products. All liabilities are borne by the user. LEWCO does not take any responsibility for misuse of these products. LEWCO recommends testing before use.

S1500SA2-10152015MH