



6859 Renoir Avenue
Baton Rouge, LA 70806

Tel: (225) 924-3221
Fax: (225) 927-2918

LEWCO 1700SA-2L Silicone Impregnated Fiberglass Fabric

Product Specifications

LEWCO Style 1700SA-2L is an asbestos free woven fiberglass fabric impregnated with a special chemical, water, and oil resistant silicone rubber. LEWCO Style 1700SA-2L is a flexible, lightweight fabric for removable insulation blankets and welding curtains.

Typical Properties

		<u>Test Method</u>
E Glass Melting Point	1523 ° F	
Maximum Temperature	500 ° F	
Minimum Temperature	-80 ° F	
Type Weave	4 Harness Satin	
Type Fiberglass	E Glass	
Weight	17.0 Oz./Sq.Yd. +/-5%	ASTM D-3776-96
Thickness	.017" Inches +/- .001	ASTM D-1777-96
Width	60 Inches	
Tensile Strength	500 * 400 W F	ASTM D-5034-95

This information is given in good faith and is believed to be accurate. It is intended for use by persons skilled in the art of fabrication and applying removable/reusable insulation or like products. All liabilities are borne by the user of this fabric. LEWCO does not take any responsibility for misuse of this product. LEWCO recommends testing before use.

S1700SA2L-10152015MH