



6859 Renoir Avenue
Baton Rouge, LA 70806

Tel: (225) 924-3221
Fax: (225) 927-2918

LEWCO 1750 SAR-2 Silicone Impregnated Fiberglass Fabric

Product Specifications

Lewco Style 1750SAR-2 is an asbestos free woven fiberglass fabric impregnated with a special chemical, water and oil resistant silicone rubber. LEWCO Style 1750SAR-2 is a flexible, light to medium fabric for welding curtains and fire blanket applications. The silicone coating is designed to prevent dust and fly. This material has been tested and meets NFPA 701-1999 Fire Tests for Flame-Resistant Textiles and Films Method 1.

Typical Properties

		<u>Test Method</u>
E-Glass Melting Point	1523 ° F	
Silicone Maximum Temperature	500 ° F	
Minimum Temperature	-80 ° F	
Type Weave	4 Harness Satin	
Color	Iron Oxide (Red)	
Type Fiberglass	E Glass	
Weight	17.5 Oz./Sq.Yd.	ASTM D-3776-96
Thickness	.0175 Inches	ASTM D-1777-96
Width	60 Inches	
Tensile Strength	500 * 400 W F	ASTM D-5034-95

This information is given in good faith and is believed to be accurate. It is intended for persons experienced in working with welding curtains or fire blankets. All liabilities are borne by the user. LEWCO recommends testing before use.

S1750SAR2-10152015MH