# **Material Safety Data Sheet**

#### LEWCO 1800HT-P & 3600HT-P

Silica Cloth

Manufacturer's Name: LEWCO Specialty Products, Inc.

6859 Renoir Avenue Baton Rouge, LA 70806

(800) 221-6414 TX & AR (800) 233-9755 (225) 924-3221 Fax (225) 927-2918

#### SECTION I – Component Date

Amorphous Silica Silicon Dioxide 7831-86-9 10 mg/m³ N/A

There is not an established threshold limit value (TLV) that is directly applicable to this family of silica materials. Chemically, these products are composed of amorphous silica with trace elements of aluminum, uranium, and iron.

The individual filament sizes of the base cloth yarn are nominally 6.0 microns and are considered "non-respirable". It will partially transform to a cristabloic structure when subjected to steady state temperatures of above 1850 F. In the event that the materials are subject to continuous temperatures exceeding 1850 F, appropriate caution should be exercised. (See Section VI).

### **SECTION III – Physical Data**

Melting Point: Not applicable Boiling Point: Not applicable

Percent Volatile by Volume: Not applicable

Specific Gravity ( $H_2O=1$ ): 2.1

Vapor Pressure (mm Hg @ 20 C): Not applicable

**Vapor Density (Air=1):** Not applicable

Evaporation Rate (Ethyl Ether=1): Not applicable

Solubility in Water: Not applicable

Appearance and Odor: White solid, no odor

pH: Not applicable

## SECTION IV - Fire and Explosion Hazard Data

Flash Point (Method Used): Not applicable Auto Ignition Temperature: Not applicable

Flammability Limits (%): LEL: NA UEL: NA Special Fire Fighting Procedures: Not applicable

**Unusual Fire and Explosion:** None

Extinguishing Media: Water, foam, carbon dioxide, dry chemical

### **SECTION IV – Health Hazard Data**

Primary Routes of Exposure: Inhalation and skin contact

Health Hazards (Including acute and chromic effects and symptoms of

overexposure):

**Acute:** <u>Inhalation:</u> Irritation of dusts and fibers may result in

inflammation of the upper respiratory tract (mouth, nose and

throat)

Skin Contact: Skin contact with dusts and fibers may produce

itching and temporary mechanical irritation.

Eye Contact: Eye contact with dusts and fibers may produce

temporary mechanical irritation

Ingestion: Temporary mechanical irritation of the digestive

tract. Observe individual if symptoms develop, consult a physician.

**Chronic:** There are no other known health effects associated with chronic

exposure to this product. (See Section I for information regarding

Quartz.)

#### **SECTION V – Emergency & First Aid Procedures**

**Inhalation:** Move individual to fresh air. Seek medical attention if irritation persists.

Skin Contact: Wash with mild soap and running water: use a washcloth to help remove

dust and fibers. To avoid further irritation do not rub or scratch irritated areas. Rubbing or scratching may force fibers into the skin. Seek medical

attention if irritation persists.

Eye Contact: Flush eyes with flowing water for at least 15 minutes. Seek medical

attention if irritation persists.

**Ingestion:** Not applicable

## **SECTION V – Employee Protection**

The following precautions are advisable during cutting and fabrication of the material, or operations that could generate dust of this material:

**Ventilation:** General dilution ventilation and/or local exhaust ventilation should be provided, as necessary to maintain exposures below PEL's or TLV's

**Respiratory Protection:** A properly fitted NIOSH/MHSA approved disposable dust respirator (TC-21C-132) should be used when: the level of dust in the air exceeds permissible exposure limits; or if irritation occurs. Use respiratory protection in accordance with your company's respiratory protection program and OSHA regulation s under CFR.

Respiratory protection is also recommended if this product is subject to steady state temperatures that exceed the 1850 F. (Use an approved high efficiency air particulate filter)

**Eye Protection:** Safety glasses, goggles or face shields should be worn whenever materials are being handled.

**Protective Clothing:** Wear loose fitting, long sleeved shirt and long pants if irritation is experienced. Wear gloves when handling this product.

Work/Hygienic Practices: Handle in accordance with good industrial hygiene and safety practices:

- Avoid unnecessary exposure to dusts and fibers
- Remove dust and fibers from the skin after exposure.
- Be careful not to rub or scratch irritated areas. Rubbing or scratching may force the fibers into the skin. The fibers should be washed off. Use of barrier creams can, in some instances, be helpful.
- Use vacuum equipment to remove fibers and dusts from clothing. Compressed air should never be used. Always wash work clothes separately and wipe out the washer/sink in order to prevent loose dust from getting on other clothes.
- Keep the work area clean of dusts and fibers generated during fabrication. Use vacuum equipment to clean up dusts and fibers. Avoid sweeping or using compressed air as these techniques resuspend dusts and fibers into the air.
- Have access to safety showers and eye wash fountains.

#### **SECTION VII – Reactivity Data**

**Stability (Conditions to avoid):** Product is stable

Incompatibility (Materials to avoid): Materials are not compatible with the basin

phosphates, hydrofluoric acids, some oxides and hydroxides; especially at elevated temperatures.

**Hazardous decomposition products:** The base fabric will partially transform to a

cristobalite structure when subjected to steady state temperatures above 1850 F. In the event it is subjected

to continuous temperatures exceeding 1850 F

appropriate caution should be exercised. (See Section

VI)

If the material is heated, residual proprietary organic ingredients contained in this product may produce smoke and irritating fumes including carbon monoxide

and carbon dioxide.

**Hazardous Polymerization:** Will not occur.

## **SECTION VIII – Storage Precautions**

Precautions to be taken in handling and storage: No special precautions necessary

#### **SECTION IX – Environmental Protection**

**Action to take for spills (Use appropriate safety equipment):** For solid product, not applicable. For dust and fibers generated during fabrication vacuum up and containerize.

**Waste Disposal Method:** Dispose in accordance with federal, state, and local regulations as a solid non-hazardous waste.

**Issue Date:** 06/21/11

Prepared By: Jamie D Guzzardo